

## 제품 사양서

<KIS-MP7000>

구분	기본사양	비고
CPU	Main: Cortex-A7 core, 900Mhz Secure: Cortex M3, 108MHz	
OS	Linux 4.1	
Memory	Flash 256 Mbyte, DDR3 256 Mbyte	
Display	4.3" 480 x 272 Pixel TFT Color LCD	
LEDs	4 LEDs	
Touch	Resistive Touch Panel	
Sound	8Ω Speaker	
MSR	ISO7812 Dual Track 2,3	
Contact	ISO7816 EMV L1 / L2	
SAM Slot	4 SAMs(6 SAM option)	
Contactless	NFC (ISO 18092),Mifare, ISO 14443 Type A, B ISO15693, NFC Forum Tag 1~4	
Serial	Serial(RS232 Level)	
USB	USB Host 1ch, USB Device 1ch	
External Memory	Micro SD Card 1ch	
Power	5V ± 5% @ 2A	
Operation Temp.	0 °C to +50 °C	
1D/2D Scanner	<b>Camera Type</b>	옵션 사항 KIS-MP7000Q 적용
Dimension	140.7mm(W) x 171.9mm(L) x 48.9mm(H) (일반, QR, 이마트 24 버전) 140.7mm(W) x 192.7mm(L) X 77.9mm(H) (키오스크 버전)	
ETC	Ethernet 1Ch	

<제품이미지>  
<KIS-MP7000>



<KIS-MP7000Q>

